



Clampstutzen DIN 32676 -ISO 2852 304L / 316L

DN	Inch	ISO	B	C	A kurz	A lang
	1/2"		25,00	12,70	12.7	28.6
	3/4"		25,00	19,00	12.7	28.6
DN 10			34,00	13,00	18.0	28.6
		DN 8	34,00	13,50	12.7	28.6
		DN 10	34,00	17,20	12.7	28.6
DN 15			34,00	19,00	18.0	28.6
		DN 15	34,00	21,30	21.5	36.0
DN 20			34,00	23,00	18.0	28.6
	1"		50,50	25,40	21.5	36.0
		DN 20	50,50	26,90	21.5	36.0
DN 25			50,50	29,00	21.5	36.0
		DN 25	50,50	33,70	21.5	36.0
DN 32			50,50	35,00	21.5	36.0
	1 1/2"		50,50	38,10	21.5	36.0
DN 40			50,50	41,00	21.5	36.0
		DN 32	50,50	42,40	21.5	36.0
		DN 40	64,00	48,30	21.5	36.0
	2"		64,00	50,80	21.5	36.0
DN 50			64,00	53,00	21.5	36.0
		DN 50	77,50	60,30	28.0	36.0
	2 1/2"		77,50	63,50	28.0	36.0
DN 65			91,00	70,00	28.0	48.0
	3"	DN 65	91,00	76,10	28.0	48.0
DN 80			106,00	85,00	28.0	48.0
		DN 80	106,00	88,90	28.0	48.0
	4"		119,00	101,60	28.0	48.0
DN 100			119,00	104,00	28.0	48.0
		DN 100	130,00	114,30	28.0	48.0
DN 125			155,00	129,00	28.0	66.0
		DN 125	155,00	139,70	28.0	66.0
DN 150			183,00	154,00	28.0	66.0
	6"		167,00	152,40	28.0	66.0
		DN 150	183,00	168,30	28.0	66.0
DN 200			233,50	204,00	28.0	66.0
		DN 200	233,50	219,10	28.0	66.0